

Technical Data Sheet	Gas booster	DLE 2-5-2 single acting, two stages, double air drive head
----------------------	--------------------	--

Available DLE series

- Single acting, single stage, single air drive head
- Double acting, single stage, single air drive head
- Double acting, single stage, double air drive head
- Single acting, two stages, single air drive head
- Single acting, two stages, double air drive head



Technical Data:

Air drive pressure pL	1-10 bar / 14.5—145 psi
Pressure ratio i	1:4 / 1:10
Compression ratio	1:25
Stage pressure ratio	1:2.5
Minimum suction pressure pA	0
Maximum suction pressure pA	1.6* air drive pressure
Maximum outlet pressure pB	100 bar
Displacement volume/double stroke	922 cm³
Maximum cycles	900 / min
Stall pressure	PB = 10*pL+2.5*pA

Standard connections

Air drive	3/4 BSP
DLE 2-5 (-GG)	Inlet/Outlet: 1/2BSP
Maximum operating temperature	60°C
Net weight	25 kg

Pressure and flow performances, please see enclosed graph.

Materials of construction hp section DLE 2-5-2:	Standard seal package	PTFE, Viton
	Compressor head	Aluminium galvanized
	HP cylinder	Hard coated aluminium
	HP piston	Aluminium
	Fittings	1.4305
	Balls	1.4034
Approximate Dimensions:	Springs	X12CrNi177
	Length	
	Width	
Available Options:	Height	
	Inert gas service (standard)	DLE 2-5-2 (-GG) (materials of construction as above indicated)
Special seal material to handle special gases on request.	Oxygen service	DLE 2-5-2-GG- <u>S</u> (Hp parts of stainless steel and oxygen cleaned)
	CO ₂ service	DLE 2-5-2-GG- <u>C</u> Seal package: PTFE, NBR
	Other inlet and outlet ports	Order codes
	Inlet: 1/2NPT Outlet: 3/8NPT	DLE 2-5-2- <u>NN</u>
Available Accessories		
Air control units for DLE series with filter pressure regulator, control pressure gauge and shut off valve	DLE 2-5-2 with C2	
To protect the booster against excessive outlet pressures or to limit the outlet pressure, a safety valve can be fitted to the air control unit in the air drive line:	DLE 2-5-2 with C2/SVair (The required outlet pressure has to be indicated.)	

Please consult factory for more information.

All technical and dimensional information subject to change. All General Terms and Conditions of sale, including limitations of our liability, apply to all products and services sold



